

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

WHAT IS CLAIMED IS:

1. Method of muffling the noise of successive components, by which an intermediate layer is placed between the two components, which are spaced away from one other at least in regions, and by which method, as a result of the intermediate layer, the sound transmission and/or vibration transmission from one component into the other is reduced, said method comprising:

inserting an air cushion (5) as an intermediate layer, and placing the air cushion at least indirectly on at least one surface respectively of each of the components (1, 2).

2. Method according to Claim 1, wherein the internal gas pressure in the air cushion (5) is increased after its installation for placing the air cushion against the components (1, 2).

3. Method according to Claim 1, wherein the internal gas pressure in the air cushion (5) is increased after the mutual connection of the two components (1, 2).

4. Method according to Claim 1, wherein the air cushion (5) is inserted with a gas volume which is no more than slight during the mounting of the two components (1, 2) to be muffled.

5. Method according to Claim 1, wherein an elastic material is selected as material for the cover of the air cushion (5) at least in regions of the cover.

6. Method according to Claim 1, wherein a muffling-active material is selected as material of the cover of the air cushion (5) at least in regions of the cover.

7. Method according to Claim 2, wherein the air cushion (5) is closed in a gastight manner after the admission of pressure.

8. Method according to Claim 1, wherein the air cushion (5) is adapted in its shape approximately to the cavity between the two components (1, 2).

9. Method according to Claim 1, in the case of a motor vehicle, particularly a passenger car or a truck, the gas space of the air cushion (5) is fluidically connected with a blower, particularly with a heater and/or an air conditioner.

10. Method according to Claim 9, wherein warm air and/or air-conditioned air is caused to flow through gas passage openings (11) arranged in the cover of the air cushion (5) into the vehicle occupant compartment of the motor vehicle.

11. Method according to Claim 1, wherein the internal pressure of the air cushion (5) is changed as a function of the frequencies to be muffled.

12. Noise absorber for successive components, which noise absorber is arranged between two components arranged away from one another at least in regions,

wherein the noise absorber is at least one air cushion (5) which is placed at least indirectly on at least one surface respectively of each of the components (1, 2).

13. Noise absorber according to Claim 12, wherein the air cushion (5) has a gas supply opening.

14. Noise absorber according to Claim 12, wherein the material of the cover of the air cushion (5) is elastic.

15. Noise absorber according to Claim 12, wherein the material of the cover of the air cushion (5) is muffling-active.

16. Noise absorber according to Claim 13, wherein the gas feeding opening can be closed in a gastight manner.

17. Noise absorber according to Claim 12, wherein the air cushion (5) is

fluidically connected with a gas-feeding blower.

18. Noise absorber according to Claim 17, wherein the cover of the air cushion has gas passage openings.

19. Noise absorber according to Claim 17, wherein in the case of a motor vehicle, particularly a passenger car or a truck, the blower is connected with the heater and/or air conditioner.

20. A passenger motor vehicle assembly comprising:

two vehicle components spaced from one another, and  
an air cushion placed between the vehicle components and  
having respective air cushion cover surface sections; and

wherein said air cushion includes an internal cavity  
connectable with a pressure source operable to increase pressure in  
the cavity and press said cover surface sections toward the  
respective components so that said cover surface sections contact  
the respective components when in an installed position thereby  
forming a sound muffling assembly between the components.

21. A passenger motor vehicle assembly according to claim 20,  
comprising a pressure source for increasing the pressure in the cavity.

22. A passenger motor vehicle assembly according to claim 21, wherein the pressure source is a blower of a vehicle air conditioning system.

23. A passenger motor vehicle assembly according to claim 22, wherein one of said components faces an interior passenger space of a vehicle.

24. A passenger motor vehicle assembly according to claim 20, wherein one of said components faces an interior passenger space of a vehicle.

25. A passenger motor vehicle assembly according to claim 20, wherein said air cushion has cover surface sections of different thickness facing the respective components.

26. A method of muffling noise transfer between two passenger vehicle components which are spaced from one another, comprising:

placing an air cushion between the vehicle components with respective air cushion cover surface sections facing respective ones of the components, and

subsequently applying pressure to said air cushion to thereby force the cover surface sections toward an operating position pressed against the vehicle components.

27. A method according to claim 26, wherein said air cushion has cover

surface sections of different thickness facing the respective components.

28. A method according to claim 26, comprising varying pressure of said air cushion independence of predetermined frequencies of sound to be muffled.

29. A method according to claim 26, wherein said applying pressure includes directing air flow from an air conditioner to said air cushion.